



# 4G Handheld Computer Specification



## Specifications

Configuration de Base	Product Model	DC - 18
	CPU	MTK6762, Octa-core 2.0Ghz / MTK6761, Quad-core 2.0Ghz
	OS Version	Android12.0
	Memory	4GB RAM+64GB ROM(MTK6762)/ 3GB RAM+32GB ROM(MTK6761)
	Bluetooth	Bluetooth 5.0
LCM	LCD	5.7 inch IPS, HD+, 720*1440
	TP	Multi-touch, IC: GT911
	Cover plate material	Corning GG3, Reinforced glass cover plate, fully fitted, 1.1mm
Network	WLAN	Support 2.4/5GHz dual-band WIFI Support 802.11ac, Wi-Fi 5
	4G wireless transferring	2G: GSM(B2/3/5/8) 3G: WCDMA (B1/2/5/8) TDS B34/39 CDMA 1X EVDO (BC0) 4G: TDD (B34/38/39/40/41) FDD (B1/2/3/5/7/8/20/26/28a&b)
Sensor	GNSS	Support GPS L1+L5/ Beidou L1+III B2A/Galileo L1+Ea5 /GLONASS/AGPS
	Motion Sensor	3-axis Accelerometer with MEMS Gyro
	Magnetometer	e Compass automatically detects direction and orientation
	Light Sensor	Automatically adjusts display backlight brightness
	NFC	Support, 13.56MHz Contactlese interface modem - ISO/IEC 18000-3、18092 - ISO/IEC 14443 A/B - ISO/IEC 15693 Mifare compliance
Camera	Front	5mp FF
	Rear	13mp AF
	Flashlight	Support
Audio	Speaker	Single speaker 8Ω, 0.8W (MAX:1W)
	Headphone	1506 waterproof headphone
	Motor	0827 flat motor
	MIC	Dual MIC, 3D DNR MIC
IO interface	Earphone	Not support
	USB	Type-C USB2.0+charging, support OTG cable, 5V/3A
	SIM Card type	Dual cards(SIM+SIM or SIM+TF)
	TF card slot	Support SIM&TF
Data Capture	Fingerprint module	Interface:SPI, Sensor: FT9371L6, up to support five fingerprints
	Scan module	100W 1D/2D code sanner
Button	Left	Custom key * 1+volume key
	Right	On/Off+Custom
Accessories	Adaptor PE+	DC 5V/2A battery charging slot *1 Overall charging slot *1 Indicator *2
	Cable	Type-C USB2.0+charging, support OTG cable, support 5V/3A
Others	Google GMS	Support
	Battery	Removable battery, 4000mAh gel polymer , 4.35V (3.8V), 10K NTC resistance
	Light indicator	1. Battery level ≤ 10%: Red light flashing, adapter red light constantly on for charging 2. 10% ≤ battery level ≤ 90%: Plug-in adapter with red light constantly on for charging 3. Battery level>90%: The green light of the adapter is constantly on for charging

	Dimension	162.5 x 77.5 x 14.6mm
	Certifications	3C certification, Drop test report, RoHS report
Environment	Operating Temperature	-20°C-60°C
	Storage Temperature	-40°C-70°C
	Working Humidity	5%-95%
	Drop Specifications	Multiple 1.2 m drops to tile over concrete
	Sealing	IP67

DISTRICODE - 6 chemin de Corbeil - 91220 Bretigny sur Orge

T. 01 64 49 60 94 - Site internet : <https://www.dstricode.com>

\*Product specifications and availability are subject to change without notice.